

## Legend Series III

### Dragon Mark III SE main speakers

Type:	Vented, quasi 4 way
Tweeter:	20mm titanium dome
Midrange:	150mm (6") Kevlar
Bass:	2 x 150mm (6") Kevlar
Frequency Response:	29Hz–25Kz
Sensitivity:	91dB/W/M
Nom. impedance:	4 Ohms
Dimensions:	W 210, D 415, H 980
Match with amplifiers:	20–200 watts

### Wizard Mark III SE main speakers

Type:	Vented, quasi 3-way
Tweeter:	20mm titanium dome
Midrange:	150mm (6") Kevlar
Bass:	150mm (6") Kevlar
Frequency Response:	34Hz–25Kz
Sensitivity:	90dB/W/M
Nom. impedance:	6 Ohms
Dimensions:	W 210, D 310, H 900
Match with amplifiers:	10–150 Watts

### Harlequin Mark III SE main speakers

Type:	Vented, quasi 3-way, magnetically shielded
Tweeter:	20mm titanium dome
Midrange:	130mm (5") Kevlar
Bass:	130mm (5") Kevlar
Frequency Response:	48Hz–25Kz
Sensitivity:	88dB/W/M
Nom. impedance:	6 Ohms
Dimensions:	W 180, D 255, H 860
Match with amplifiers:	10_120 Watts

### Legend Centre Mark III SE

Type:	Vented 2-way (D'Apolito array) magnetically shielded
Tweeter:	20mm titanium dome
Midrange:	130mm (5") Kevlar
Bass:	130mm (5") Kevlar
Frequency Response:	50Hz–25Kz
Sensitivity:	87dB/W/M
Nom. impedance:	6 Ohms
Dimensions:	W 600, D 248, H 150

### Legend Rear Mark III SE

Type:	Sealed 2-way wall mount magnetically shielded
Tweeter:	20mm titanium dome
Mid/bass:	130mm (5") Kevlar
Frequency Response:	65Hz–25Kz
Sensitivity:	86dB/W/M
Nom. impedance:	6 Ohms
Dimensions:	W 355, D 115, H 300

### Thor Mark IV powered subwoofer

Purpose:	Home theatre/music reinforcement Suits rooms 40m <sup>3</sup> and above
Enclosure:	Dual vented, full acoustic damping, full perimeter bracing
Driver:	Low mass 300mm (12") cone, Air-vented 4-layer 50mm diameter Kapton VC, extended travel suspension, Low-Q 300W long- term max. power, 32mm useable excursion
Amplifier:	200 Watts RMS, <0.002% THD, auto on, 0°/180° phase switch, crossover bypass, Thermal/soft clipping protection, Low/High level operation
Freq. Response:	19Hz–180Hz
Dimensions (mm):	W 440, D 470, H 510

### Krakatoa powered subwoofer

Purpose:	Home theatre/music reinforcement Suits Rooms to 60m <sup>3</sup>
Enclosure:	Dual vented, full acoustic damping, full perimeter bracing
Driver:	Low mass 250mm (10") cone, Ultra high excursion technology High temp 50mm Kapton voice coil
Amplifier:	100 Watts RMS, <0.009% THD, 0°/180° phase switch, auto on, thermal/soft clipping protection, Low/high level operation
Frequency Response:	22Hz–180Hz
Dimensions (mm):	W 390, D 420, H 390