

## Legend Series IV

### Dragon Series IV main speakers

Type:	Vented, quasi 4 way Floorstand
Real wood finish	WA Jarrah / Black Tasmanian Oak
Impedance:	Nom. 4 Ohms
Frequency Response:	30–36K Hz
Sensitivity:	91 (dB/W/M)
Dimensions: (mm)	H1050 x W275 x D500    Weight 33kg ea
Match with Amplifier	10–200 Watts RMS (dual wired for twin-amp input)
Bass	165mm Composite Cone Technology
Bass/Mid	165mm, Frequency Extending Phase dome, Composite Cone Technology
Tweeter	30mm Precision Ribbon

### Unicorn Series IV centre speaker

Type:	Vented, Symmetric Array, 2-way Centre
Real wood finish	WA Jarrah / Black Tasmanian Oak
Impedance:	Nom. 6 Ohms
Frequency Response:	48Hz–36KHz
Sensitivity:	90 (dB/W/M)
Dimensions: (mm)	H200 x W700 X D300    Weight 16Kg ea
Bass/Mid	2x 165mm, Frequency Extending Phase domes, Composite Cone Technology
Tweeter	30mm Precision Ribbon

### Hydra Series IV rear speakers

Type:	Sealed, 2 way, wall-mount Rear Effects
Real wood finish	Black Tasmanian Oak
Impedance:	Nom. 8 Ohms
Frequency Response:	68–36K Hz
Sensitivity:	87 (dB/W/M)
Dimensions: (mm)	H400 x W320 x D130    Weight 6kg ea
Bass/Mid	165mm, Frequency Extending Phase dome, Composite Cone Technology
Tweeter	30mm Precision Ribbon

### Thor Series IV powered subwoofer

Purpose:	Home theatre/music reinforcement Suits rooms 40m <sup>3</sup> and above
Enclosure:	Dual vented, full acoustic damping, full perimeter bracing
Driver:	Low mass 300mm (12") cone, Air-vented 4- layer 50mm diameter Kapton VC, extended travel suspension, Low-Q 300W long-term max. power, 32mm useable excursion
Amplifier:	200 Watts RMS, <0.002% THD, auto on, 0°/180° phase switch, crossover bypass, Thermal/soft clipping protection, Low/High level operation
Freq. Response:	19Hz–180Hz
Dimensions (mm):	W 440, D 470, H 510

### Wizard Series IV main speakers

Type:	Vented, quasi 3 way Floorstand
Real wood finish	WA Jarrah / Black Tasmanian Oak
Impedance:	Nom. 6 Ohms
Frequency Response:	35–36K Hz
Sensitivity:	90 (dB/W/M)
Dimensions: (mm)	H950 x W250 x D430    Weight 25Kg ea
Match with Amplifier	10–150 Watts RMS
Bass	165mm Composite Cone Technology
Bass/Mid	165mm, Frequency Extending Phase dome, Composite Cone Technology
Tweeter	30mm Precision Ribbon

### Merlin Series IV bookshelf speakers

Purpose:	Home theatre/music reinforcement Suits rooms 40m <sup>3</sup> and above
Enclosure:	Dual vented, full acoustic damping, full perimeter bracing
Driver:	Low mass 300mm (12") cone, Air-vented 4-layer 50mm diameter Kapton VC, extended travel suspension, Low-Q 300W long-term max. power, 32mm useable excursion
Amplifier:	200 Watts RMS, <0.002% THD, auto on, 0°/180° phase switch, crossover bypass, Thermal/soft clipping protection, Low/High level operation
Freq. Response:	19Hz–180Hz
Dimensions (mm):	W 440, D 470, H 510

### Krakatoa Series IV powered subwoofer

Purpose:	Home theatre/music reinforcement Suits Rooms to 60m <sup>3</sup>
Enclosure:	Dual vented, full acoustic damping, full perimeter bracing
Driver:	Low mass 250mm (10") cone, Ultra high excursion technology High temp 50mm Kapton voice coil
Amplifier:	100 Watts RMS, <0.009% THD, 0°/180° phase switch, auto on, thermal/soft clipping protection, Low/high level operation
Frequency Response:	22Hz–180Hz
Dimensions (mm):	W 390, D 420, H 390