

## Legend Series V



### Dragon Series V main speakers

Vented quasi 4-way Floor standing	Enclosure ....Dual bass reflex
Impedance ....4 Ohms	Rec. Amplifier Power .....Home Theatre 150–500, Two-channel 20–500 WRMS
Frequency Response .....25 Hz–25 KHz	Dimensions....1050H x 400D X 220W
Sensitivity....91 (dB/W/M)	Connector ..dual gold-plated binding posts (bi-wire capable)
Bass / Mid ...3 x 130 mm (EPD*) sealed composite paper/fibre cone, inverted cap.	Available Finishes.....Jarrah / Black Oak
Tweeter.....25mm soft dome, neodymium magnet.	Weight.....25.1 KG each speaker



### Wizard Series V main speakers

Vented quasi 3-way floor standing	Enclosure ....Bass reflex
Impedance ....4 Ohms	Rec. Amplifier Power .....Home Theatre 100–250, Two-channel 20–250 WRMS
Frequency Response .....32 Hz–25 KHz	Dimensions....970H x 350D X 205W
Sensitivity....90 (dB/W/M)	Connector ..dual gold-plated binding posts (bi-wire capable)
Bass / Mid.....2 x 130 mm (EPD*) sealed composite paper/fibre cone, inverted cap.	Available Finishes.....Jarrah / Black Oak
Tweeter.....25mm soft dome, neodymium magnet.	Weight 20 KG each speaker



### Harlequin Series V main speakers

Vented quasi 3-way floor standing	Rec. Amplifier Power .....Home Theatre 100–200, Two-channel 15–200 WRMS
Impedance ....4 Ohms	Dimensions....900H x 280D X 190W
Frequency Response .....35 Hz–25 KHz	Connector ..dual gold-plated binding posts (bi-wire capable)
Sensitivity....89 (dB/W/M)	Available Finishes.....Jarrah / Black Oak
Bass / Mid ...2 x 105 mm (EPD*) sealed composite paper/fibre cone, inverted cap.	Weight.....16 KG each speaker
Tweeter.....25mm soft dome, neodymium magnet.	Enclosure ....Bass reflex



### Mentor Series V main speakers

Vented 2-way Bookshelf	Rec. Amplifier Power .....Home Theatre 50–150, Two-channel 15–150 WRMS
Impedance ....6 Ohms	Dimensions....375H x 290D X 205W
Frequency Response .....47 Hz–25 KHz	Connector ..dual gold-plated binding posts (bi-wire capable)
Sensitivity....88 (dB/W/M)	Available Finishes.....Jarrah / Black Oak
Bass / Mid ...130 mm (EPD*) sealed com- posite paper/fibre cone, inverted cap.	Weight.....7.5 KG each speaker
Tweeter.....25mm soft dome, neodymium magnet.	Enclosure ....Bass reflex

## Legend Series V

### Merlin Series V rear speakers



Vented 2-way Bookshelf  
 Impedance ....6 Ohms  
 Frequency Response .....55 Hz–25 KHz  
 Sensitivity....87 (dB/W/M)  
 Bass / Mid ...105 mm (EPD\*) sealed composite paper/fibre cone, inverted cap.  
 Tweeter.....25mm soft dome, neodymium magnet.  
 Enclosure ....Bass reflex

Rec. Amplifier Power .....Home Theatre 50–150, Two-channel 15–150 WRMS  
 Dimensions....320H x 230D X 180W  
 Connector ..Dual Gold Plated Binding Posts (bi-wire capable)  
 Available Finishes.....Jarrah / Black Oak  
 Weight.....6 KG each speaker  
 Mounting choices.....free-standing; 1/4" threaded insert for wall bracket; or optional Richter stands

### Thor Series V powered subwoofer

Dual Vented Active 12" Subwoofer  
 Frequency Response .....<19Hz–120Hz (Music mode at lowest frequency crossover setting)  
 Amplifier.....Digital class D amplifier true 300W RMS  
 Control and signal processing Fully Digital (Analogue devices DSP)

Driver.....300W, 255 mm (EPD\*) sealed composite paper/fibre cone, inverted cap, ultra high excursion with large neoprene roll surround, double magnet gap assembly, air vented.  
 Dimensions....510H x 430D X 440W  
 Finish .....Black Oak  
 Weight 28KG



### Griffin Series V centre speaker



Vented Symmetric Array 2-Way Centre  
 Impedance ....4 Ohms  
 Frequency Response .....48 Hz–25 KHz  
 Sensitivity....89 (dB/W/M)  
 Bass / Mid ...2 x 105 mm (EPD\*) sealed composite paper/fibre cone, inverted cap.  
 Tweeter.....25mm soft dome, neodymium magnet.

Enclosure ....Bass reflex  
 Rec. Amplifier Power .....Depends on main speakers  
 Dimensions .165H x 385D X 495W  
 Connector ..Dual Gold Plated Binding Posts (bi-wire capable)  
 Available Finishes.....Jarrah / Black Oak  
 Weight 10 KG

\* Effective piston diameter (EPD); Images not to scale.