

Specifications

Precious Metals



All woofers and tweeters are double-magnet ■ rear speakers are rated at 8 ohms; centres and floor standing models at 6 ohms ■ all speakers fully magnetically shielded (prevents interference with TV/monitors) ■ all crossovers use high quality inductors and polypropylene capacitors ■ all front speakers are 3-way ■ all centres & rears are 2-way ■ all tweeters 25mm soft dome ■ *dimensions w x h x d in mm.

REC. SYSTEM POWER	301 60–120w	401 70–150w	501 80–200w
FRONT	301	401	501
Drivers	2 x 90mm 1 x tweeter	2 x 101mm 1 x tweeter	2 x 125mm 1 x tweeter
Sensitivity (dB/W/M)	88	88	89
Response(Hz)	79–20,000	65–20,000	50–20,000
Dimensions	135 x 910 x 145*	155 x 990 x 165*	190 x 1050 x 200*
CENTRE	301	401	501
Drivers	2 x 90mm 1 x tweeter	2 x 101mm 1 x tweeter	2 x 125mm 1 x tweeter
Sensitivity (dB/W/M)	89	89	89
Response(Hz)	90–20,000	90–20,000	68–20,000
Dimensions	460 x 135 x 145*	495 x 155 x 165*	585 x 190 x 200*
REAR	301	401	501
Drivers	1 x 90mm 1 x tweeter	1 x 101mm 1 x tweeter	1 x 125mm 1 x tweeter
Sensitivity (dB/W/M)	88	88	88.5
Response(Hz)	90–20,000	85–20,000	85–20,000
Dimensions	135 x 250 x 145*	155 x 255 x 165*	190 x 300 x 200*
SUBWOOFERS	PM-SW101	PM-SW121	
Power (RMS)	100w (active)	200w (active)	
Response (Hz)	22–180	19–180	
Distortion	<0.009% (typical)	<0.002%	
Protection	— thermal/soft clipping —		
Driver	250mm	300mm	
	— featuring ultra-high-excursion technology —		
Voice coil	— high temperature 50mm Kapton —		
Dimensions	390 x 390 x 420*	440 x 530 x 460*	