

Sovereigns

Emperor main speakers

Woofers:	Two 165mm carbon fibre
Midrange:	Two 165mm polypropylene
Tweeter:	25mm doped cotton dome, ferro fluid cooling
Cable:	Internally hardwired with TARA LABS® Klara cable
Enclosure:	70 litre bass reflex, two 7-litre vented midrange, time-aligned front baffle
Frequency response:	(-6dB) 29Hz–20kHz ± 2.5dB
Sensitivity:	92dB
Impedance:	Nominal 4 Ohms
Rec. amp power:	35–200 watts RMS
Dimensions (mm):	H 1050 W 275 D 395

Chancellor main speakers

Woofers:	Two 165mm carbon fibre
Midrange:	Two 130mm polypropylene
Tweeter:	25mm doped cotton dome, ferro fluid cooling
Cable:	Internally hardwired with TARA LABS® Klara cable
Enclosure:	60 litre bass reflex, two 1.5-litre sealed midrange, time-aligned front baffle
Frequency response:	(-6dB) 33Hz–20kHz ± 2.5dB
Sensitivity:	91dB
Impedance:	Nominal 4 Ohms
Rec. amp power:	35–175 watts RMS
Dimensions (mm):	H 965 W 245 D 360

Regent main speakers

Woofers:	Two 165mm carbon fibre
Midrange:	165mm polypropylene
Tweeter:	25mm doped cotton dome, ferro fluid cooling
Cable:	Internally hardwired with TARA LABS® Klara cable
Enclosure:	40 litre bass reflex, 7 litre vented midrange, time-aligned front baffle
Frequency response:	(-6dB) 37Hz–20kHz ± 2.5dB
Sensitivity:	91dB
Impedance:	Nominal 4 Ohms
Rec. amp power:	35–150 watts RMS
Dimensions (mm):	H 880 W 225 D 330

Baron main speakers

Woofers:	Two 165mm carbon fibre
Midrange:	130mm polypropylene
Tweeter:	25mm doped cotton dome, ferro fluid cooling
Cable:	Internally hardwired with TARA LABS® Klara cable
Enclosure:	30 litre bass reflex, 1.5 litre sealed midrange, time-aligned front baffle
Frequency response:	(-6dB) 40Hz–20kHz ± 2.5dB
Sensitivity:	90dB
Impedance:	Nominal 4 Ohms
Rec. amp power:	35–125 watts RMS
Dimensions (mm):	H 795 W 205 D 295

Envoy effect/rear speakers

Mid/woofer:	165mm polymer coated
Tweeters:	Twin 25mm dome, ferro fluid cooling
Enclosure:	6.5 litre wall-mounting infinite baffle, wool damping
Frequency response:	75Hz–20kHz
Sensitivity:	88.5dB
Impedance:	8 Ohms
Rec. amp power:	20–150 watts RMS
Dimensions (mm):	H 315 W 420 D 125

Ambassador centre speaker

Mid/woofer:	Twin 165mm polymer coated
Tweeter:	25mm dome, ferro fluid cooling
Cable:	High performance TARA LABS® Klara cable
Enclosure:	45 litre twin-vented, comour driver surround, 32mm ultra-stable baffle
Frequency response:	29Hz–20kHz
Sensitivity:	90dB
Impedance:	4 Ohms
Rec. amp power:	20–150 watts RMS
Dimensions (mm):	H 225 W 650 D 425